

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Industrial, carpet, plumbing, HVAC, sealing, waterproofing, patching and asbestos abatement applications

## ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Conformable
- > Good handling characteristics – does not twist or curl during application
- > Wide variety of colors

## CONSTRUCTION

**Overall Grade/Function:** General Purpose

**Backing:** Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

**Adhesive:** Natural rubber



## COLOR(S)

	Black (BLK)		Brown (BRN)		Orange (ORG)		Burgundy (BRG)
	Blue (BLU)		Floral Green (FGN)		Purple (PRP)		Silver (SIL)
	Beige (BEI)		Green (GRN)		Olive Drab (OLV)		Red (RED)
	White (WHI)		Yellow (YEL)				

## STANDARD WIDTH(S)

48 mm    72 mm

## STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	9 mils	0.23 mm
Dielectric Strength	6.0 KV	
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.